

# THERMOCOUPLES

for use with Reflow Tracker system

## PA0210 FAST RESPONSE EXPOSED JUNCTION

This is the standard thermocouple used throughout the reflow industry and is constructed from type K thermocouple wire. Each conductor is PTFE insulated and then twisted together to prevent tangling in use. The wire diameter is 0.2mm providing a good compromise between size and strength. The thermocouple tip is pre tinned to ease soldering to the PCB. We recommend the use of an activated flux and high temperature solder to attach this thermocouple to the PCB assembly.

|                               |   |
|-------------------------------|---|
| <b>Thermocouple Material:</b> | Type K Special Limits of Accuracy                                       |
| <b>Accuracy:</b>              | $\pm 1.1^{\circ}\text{C}$ or 0.4% of the reading (whichever is greater) |
| <b>Length:</b>                | 800mm*  |
| <b>Conductor Diameter:</b>    | 0.2mm   |
| <b>Temperature:</b>           | 265°C maximum   |

\*Other lengths available on request

## PA1683 FINE WIRE

This thermocouple has been developed specifically for use with BGA and ultra fine pitch surface mount components. The type K thermocouple conductors are 0.1mm in diameter, each insulated with PTFE. The two conductors are then over-wrapped with a single outer PTFE sheath to prevent tangling in use. The recommended attachment method is activated flux and high temperature solder. For BGA, the accepted practice is to drill through the PCB and insert the tip until it touches a ball and then bond the thermocouple wire in place.

|                               |   |
|-------------------------------|---|
| <b>Thermocouple Material:</b> | Type K to British Standard Class I                                      |
| <b>Accuracy:</b>              | $\pm 1.5^{\circ}\text{C}$ or 0.4% of the reading (whichever is greater) |
| <b>Length:</b>                | 500mm   |
| <b>Conductor Diameter:</b>    | 0.1mm   |
| <b>Temperature:</b>           | 265°C maximum   |

## PA1571 ULTRA FINE DIAMETER MINERAL INSULATED

The PA1571 is intended for use in high temperature applications. It is a Type K Mineral Insulated thermocouple with an Inconel outer sheath. The overall diameter is 0.5mm. It can operate to 1,000°C. Attachment method will depend on the application but can include ceramic cement or mechanical fixtures.

|                               |   |
|-------------------------------|---|
| <b>Thermocouple Material:</b> | Type K to British Standard Class I                                      |
| <b>Accuracy:</b>              | $\pm 1.5^{\circ}\text{C}$ or 0.4% of the reading (whichever is greater) |
| <b>Length:</b>                | 600mm   |
| <b>Conductor Diameter:</b>    | NA (outer sheath is 0.5mm)  |
| <b>Temperature:</b>           | 1,000°C maximum   |

## PA0215 FIBRE INSULATED PROBE

Exposed junction type K thermocouple constructed from 0.2mm wire with glass fibre insulation. This probe is designed for continuous use up to 500°C and is therefore ideally suited to high temperature soldering applications. For best results we recommend that the probe is attached using an activated flux and high temperature solder.

|                               |   |
|-------------------------------|---|
| <b>Thermocouple Material:</b> | Type K Special Limits of Accuracy                                       |
| <b>Accuracy:</b>              | $\pm 1.1^{\circ}\text{C}$ or 0.4% of the reading (whichever is greater) |
| <b>Length:</b>                | 800mm   |
| <b>Conductor Diameter:</b>    | 0.2mm   |
| <b>Temperature:</b>           | 500°C maximum   |

**Europe and Asia**  
 DATAPAQ Limited,  
 Deanland House, 160 Cowley Road,  
 Cambridge CB4 0GU, UK  
 Tel: +44 (0)1223 423 141  
 Fax: +44 (0)1223 423 306  
 e-mail: sales@datapaq.co.uk  
 Web: www.datapaq.com

**North and South America**  
 DATAPAQ Inc.  
 187 Ballardvale Street  
 Wilmington, MA 01887, USA  
 Tel: +1 978 988 9000  
 Fax: +1 978 988 0666  
 e-mail: sales@datapaq.com  
 Web: www.datapaq.com

**Germany**  
 DATAPAQ GmbH  
 Valdorfer Straße 100  
 D-32602 Vlotho, Deutschland  
 Telefon: +49 5733 9107 0  
 Fax: +49 5733 9107 27  
 e-mail: sales@datapaq.de  
 Web: www.datapaq.de



Due to continuing product improvements, specifications are subject to change without prior notice.  
 thermocouples-Q18.qxp - Iss 02 - JULY07